

IN THE CLAIMS:

Please cancel claims 1-7 without prejudice or disclaimer

1           8. (new) A rotor for an electric rotary machine comprising:  
2           a rotor yoke having a cylindrical peripheral wall with a first axial end and a  
3           second axial end opposite the first axial end, a bottom wall provided integrally with  
4           said peripheral wall so as to close the first axial end of said peripheral wall, and a  
5           boss provided at a central portion of said bottom wall for mounting a rotary shaft,  
6           said peripheral wall further comprising an inner surface and an outer surface, and a  
7           protrusion means formed on said outer surface; and  
8           an inductor forming member fitted onto the outer surface of said peripheral  
9           wall, said inductor forming member having a ring-like portion formed on an outer  
10          surface of said ring-like portion and an inner surface of said ring-like portion fitted  
11          against the outer surface of said peripheral wall of the rotor yoke, said ring-like  
12          portion having a first axial end and a second axial end opposite the first axial end of  
13          the ring-like portion,  
14          wherein said protrusion means is located against the first axial end of said  
15          ring-like portion and the second axial end of said ring-like portion when said ring-like  
16          portion is fitted against said peripheral wall of the rotor yoke.

1           9. (new) A rotor for an electric rotary machine as set forth in claim 8, wherein  
2           said protrusion means comprises at least one embossed portion extending from the  
3           peripheral wall of said rotor yoke, wherein said embossed portion is located against  
4           the first axial and the second axial end of said ring-like portion when said ring-like  
5           portion is fitted against said peripheral wall of the rotor yoke.

1           10. (new) A rotor for an electric rotary machine comprising  
2           a rotor yoke having a cylindrical peripheral wall with a first axial end and a  
3           second axial end opposite the first axial end, a bottom wall provided integrally with  
4           said peripheral wall so as to close the first axial end of said peripheral wall, and a

5 boss provided at a central portion of said bottom wall for mounting a rotary shaft,  
6 said peripheral wall further comprises an inner surface and an outer surface,  
7 at least one first outer peripheral area of a first outside diameter, at least one  
8 second outer peripheral area of a second outside diameter smaller than said first  
9 outer peripheral area with a shoulder extending in a radial direction from said  
10 second outer peripheral area to first outer peripheral area, and at least one third  
11 outer peripheral area of a third outside diameter smaller than said second outer  
12 peripheral area with at least one protrusion projecting from the peripheral wall  
13 between said second outer peripheral area and said third outer peripheral area,  
14 said first outer peripheral area, said second outer peripheral area, and said third  
15 outer peripheral area provided sequential in order in an axial direction of said rotor  
16 yoke; and

17 an inductor forming member fitted onto the outer surface of said peripheral  
18 wall, said inductor forming member having a ring-like portion formed on an outer  
19 surface of said ring-like portion, said ring-like portion having a first axial end and a  
20 second axial end opposite the first axial end of the ring-like portion, and an inner  
21 surface of said ring-like portion fitted against the outer surface of said peripheral  
22 wall of the rotor yoke,

23 wherein said shoulder is located against the first axial end of said ring-like  
24 portion and said protrusion is against the second end of the ring-like portion when  
25 said ring-like portion is fitted against said peripheral wall of the rotor yoke.

1 11. (new) A rotor for an electric rotary machine comprising:

2 a rotor yoke having a cylindrical peripheral wall with a first axial end and a  
3 second axial end opposite the first axial end, a bottom wall provided integrally with  
4 said peripheral wall so as to close the first axial end of said peripheral wall, and a  
5 boss provided at a central portion of said bottom wall for mounting a rotary shaft,  
6 and

7 an inductor forming member fitted onto the outer surface of said peripheral  
8 wall, said inductor forming member having a ring-like portion formed on an outer  
9 surface of said ring-like portion, said ring-like portion having a first axial end and a

10 second axial end opposite the first axial end of the ring-like portion, and an inner  
11 surface of said ring-like portion fitted against the outer surface of said peripheral  
12 wall of the rotor yoke,

13 said peripheral wall further comprises an inner surface and an outer surface  
14 and at least one protrusion on the outer surface of the peripheral wall, said  
15 protrusion including a first protrusion portion extending in an axial direction of said  
16 rotor yoke and a second protrusion portion extending in a circumferential direction of  
17 said rotor yoke at a first end of said first protrusion portion, said first protrusion  
18 portion including a projection extending from a second end of said first protrusion  
19 portion,

20 said inner surface of said ring-like portion further comprising at least one  
21 recess corresponding to each first protrusion portion so that each first protrusion  
22 portion is engaged with a corresponding recess,

23 wherein said second protrusion portion is located against the first axial end of  
24 said ring-like portion and said projection is against the second axial end of the ring-  
25 like portion when said ring-like portion is fitted against said peripheral wall of the  
26 rotor yoke.

1 12. (new) A rotor for an electric rotary machine as set forth in claim 11,  
2 wherein said second protrusion portion is integrally formed with said first protrusion  
3 portion so that said protrusion is T-shaped.

1 13. (new) A rotor for an electric rotary machine comprising  
2 a rotor yoke having a cylindrical peripheral wall with a first axial end and a  
3 second axial end opposite the first axial end, a bottom wall provided integrally with  
4 said peripheral wall so as to close the first axial end of said peripheral wall, and a  
5 boss provided at a central portion of said bottom wall for mounting a rotary shaft,  
6 and

7 an inductor forming member fitted onto the outer surface of said peripheral  
8 wall, said inductor forming member having a ring-like portion formed on an outer  
9 surface of said ring-like portion, said ring-like portion having a first axial end and a

10 second axial end opposite the first axial end of the ring-like portion, and an inner  
11 surface of said ring-like portion fitted against the outer surface of said peripheral  
12 wall of the rotor yoke,  
13 said peripheral wall further comprises an inner surface and an outer surface  
14 and at least one protrusion on the outer surface of the peripheral wall, said  
15 protrusion having a pair of protrusion portions extending in an axial direction of said  
16 peripheral wall, said pair being located faced to each other at a distance slightly  
17 larger than an axial size of said ring-like portion,  
18 said inner surface of said ring-like portion further comprising at least one  
19 recess corresponding to each protrusion so that each protrusion is engaged with a  
20 corresponding recess,  
21 wherein said pair is located against the first axial end of said ring-like portion  
22 and the second axial end of the ring-like portion when said ring-like portion is fitted  
23 against said peripheral wall of the rotor yoke.

1 14. (new) A rotor for an electric rotary machine as set forth in either of claims  
2 8, 9, 10, 11, 12, and 13, wherein a permanent magnet forming a magnetic field  
3 system is mounted on the inner surface of said peripheral wall of said rotor yoke.

#### REMARKS

Applicant thanks the examiner for the careful examination given to the present application. The application has been reviewed in light of the Office action and amended as necessary to more clearly and particularly claim the subject matter which Applicant regards as the invention. It is respectfully submitted that the application is patentable over the art of record. Reconsideration of the application as amended is respectfully requested.

Claims 1-7 have been canceled and new claims 8-14 have been added to more clearly define the invention.